

Specification

	0.5 Gallon	1 Gallon	1.5 Gallon
Working Capacity	0.5 Gal., 2L	1 Gal., 4L	1.5 Gal., 5L
Tank Volume	0.8 Gal., 3L	1.3 Gal., 5L	2.0 Gal., 7.5 L
Tank Material	AISI 304		
Max. Working Pressure	90 psi 6 bar		
Filling Mouth	Ø2.75 inch (Ø70mm)		
Pressure Relief Valve	Max at 60 psi 4 bar,		
Pressure Gauge	0-100 psi 7 bar		
Pump Handle	Brass, D-type		
Pump Cylinder	AISI 304 SS tubing with Viton™ check-valve		
Hose	48 in (120 cm)		
Trigger Valve	brass, drip-free (DFC) type with locking nut		
Wand	AISI 304, Stainless Steel core, Tig Welded and Argon Purge		
Nozzle	4-way multi-nozzle with crack & crevice extension straw		
Carrying Strap	Single shoulder strap optional;		
Service Kit	Pump & Valve extension/trigger service kit, Includes seal/gasket kit		
Tank Dimensions	Ø6.7 x H7.3 in (Ø17 x H18.5 cm)	Ø6.7 x H11.2 in (Ø17 x H28.5 cm)	Ø6.7 x H14.2 in (Ø17 H36 cm)
Total Height	10.6 in (27 cm)	14.6 in (37 cm)	17.5 in (44.5 cm)
Net Weight	5.72 pound (2.6 kg)	6.82 pound (3.1 kg)	8.14 pound (3.7 kg)

※ Specifications subject to change without notice or obligation. Trademarks appearing within are the property of Airofog USA, Ltd. Other trademarks are the property of their respective owners.

Model example -ProLine A4DFC9-
A: available for worldwide
4: 1 Gal. (4L) tank; 2: 0.5 Gal. (2L) tank; 5: 1.5 Gal. (5L) tank DFC-VE: drip-free trigger valve with cable
9: 7.5" wand ; 18:17.5" wand 24" 36"
M: multi-nozzle CC ; F: fan nozzle